



Superior Safes are a new product built in a timeless fashion. They are without equal in their commitment to the highest standard of excellence. This is best seen in Superior's additional levels of fire protection and door construction. But keeping treasured items secure is only the beginning as Superior Safes are beautiful examples of high quality craftsmanship which would be a terrific addition to any room. All it takes is one look to realize that Superior Safes are a Step Above the Rest.

Supreme Series



The Supreme Series safes are truly the ideal in safe production, containing more steel than any other safe in the industry. Their unparalleled structure includes a triple-step door with three heat-expanding seals, four layers of fire protection, and a glass relock system. Finally, the unsurpassable radius door edges and luxurious standard of two-tone finish set them apart as the ultimate safe.

Features

Maximum Security Door

- Exclusive Triple-Step™ door
- 1/2" thick steel-plate door
- 3/16" inner-door plate

Body

- 3/16" thick outer steel wall
- Triple-Step™—3 fire-seals
- Up to 4 layers of 5/8" firewall

Boltworks

- Four-way active boltworks
- Up to 18-1 1/2" active bolts
- Internal Locking Detent™

Ratings

- ASME certified fire protection
- 1865°F 110-minute fire rating
- UL Security rating

Specifications

Safe Model	Dimensions WxHxD	Outer Shell Thickness	Total Depth	Volume (Cubic Feet)	Approx. Weight	Active Bolt	Door Plate Thickness	Body Thickness
S-55	45 1/2" x 73" x 28"	3/16"	30"	55 CF	1725 lbs	18-1 1/2"	1/2"	2 3/4"
S-45	39 1/2" x 67" x 28"	3/16"	30"	45 CF	1450 lbs	16-1 1/2"	1/2"	2 3/4"

Regal Series



Features

Maximum Security Door

- Exclusive Triple-Step™ door
- 3/8" thick steel-plate door
- 10 ga. inner-door plate

Body

- 10 ga. thick outer steel wall
- Triple-Step™—3 fire-seals
- Up to 4 layers of 5/8" firewall

Boltworks

- Four-way active boltworks
- Up to 18–1 1/4" active bolts
- Internal Locking Detent™

Ratings

- ASME certified fire protection
- 1500°F 90-minute fire rating
- UL Security rating

Regal Series safes boast the same triple-step door design, beautiful radius edges, and size options as those of the Supreme Series. These stately safes come equipped with ASME certified fire protection at 1500°F for 90 minutes. Their ten gauge exterior serves as the finishing touch for a safe that is king of its class.

Specifications

Safe Model	Dimensions WxHxD	Outer Shell Thickness	Total Depth	Volume (Cubic Feet)	Approx. Weight	Active Bolt	Door Plate Thickness	Body Thickness
R-55	45 1/2" x 73" x 28"	10 ga.	30"	55 CF	1525 lbs	18–1 1/4"	1/2"	2"
R-45	39 1/2" x 67" x 28"	10 ga.	30"	45 CF	1350 lbs	16–1 1/4"	1/2"	2"
R-35	33 1/2" x 67" x 26"	10 ga.	28"	35 CF	1150 lbs	16–1 1/4"	1/2"	2"

Master Series



Features

Maximum Security Door

- Exclusive Double-Step™ door
- 1/4" thick steel-plate door
- 12 ga. inner-door plate

Body

- 12 ga. thick outer steel wall
- Double-Step™—2 fire-seals
- Up to 3 layers of 5/8" firewall

Boltworks

- Four-way active boltworks
- Up to 16-1" active bolts
- Internal Locking Detent™

Ratings

- ASME certified fire protection
- 1500°F 60-minute fire rating
- UL Security rating

Unlike others of its class, the Master Series safes have unprecedented features. The three-size series offers a double-step door design, active bolts on all four sides, and three levels of fire protection on the top and two on the sides. The Master is a classic edition, more than qualified to keep your collections safe.

Specifications

Safe Model	Dimensions WxHxD	Outer Shell Thickness	Total Depth	Volume (Cubic Feet)	Approx. Weight	Active Bolt	Door Plate Thickness	Body Thickness
S-50	41"x72 1/2"x27"	12 ga.	29"	50 CF	1150 lbs	16-1"	1/4"	1 3/8"
S-35	37"x60 1/2"x27"	12 ga.	29"	35 CF	925 lbs	14-1"	1/4"	1 3/8"
S-25	31"x60"x26"	12 ga.	26"	25 CF	800 lbs	14-1"	1/4"	1 3/8"

Features

Triple-Step™ Protection

Superior builds safes the old fashioned way: heavy and tough; bank vault tough. In today's marketplace not all safes are created equal. Compare Superior Safes, feature for feature, with other safes on the market. Examine Superior's design, construction, overall quality and affordable pricing. We're confident you'll find our safes to be of the highest excellence.

Fire Protection

Superior Safes set new fire protection standards. Superior's exclusive Double-Step™ and Triple-Step™ door design, with multiple heat-expanding door seals, provides unsurpassed fire protection.

Three levels of fire protection

- I. 60 minutes at 1500°F—Master Series
- II. 90 minutes at 1500°F—Regal Series
- III. 110 minutes at 1865°F—Supreme Series

Color Options

 Antique Bronze	 Burgandy	 Granite
 Silver Birch	 Black	 Sand
 Midnight Cherry	 Midnight Blue Metallic	 Jade
 Gun Smoke	 Forest Green Metallic	 Ivory

Warranty

Superior Safe Company warrants each new safe to be free from defects in material and workmanship for the lifetime of the original purchaser. Superior Safe will repair or replace (at our option) any safe broken into by forced entry, or damaged by unlawful break-in attempt or damaged in a fire. Superior Safe will have a dealer or locksmith assess the damage and determine whether the safe can be repaired. Superior Safe will cover the shipping charges. Superior Safe electronic locks are covered for two years; mechanical locks are covered by a lifetime warranty. See written warranty for specific details.